

INDEX

- AgDrone System™, 9–10
Agricultural machinery, 20
Agrochemicals, 21, 25–27
advantages of, 25–26
disadvantages of, 26–27
Agroptima, 12, 14
Agrotechnology, 81–83
Agrotechnology solutions,
 111–116
 aim and objectives,
 116–117
 feasibility analysis,
 157–161
 proof-of-concept
 activities, 118–141
Agrownin, 11, 14
Aguascalientes, 35
Aguasmarket, 12, 14
Arduino Mega 2560, 59,
 67, 74–75, 76–77,
 118–119, 122–124,
 126–127, 129–130,
 133–134, 136–140,
 145–147, 155–157,
 160–161, 163, 164,
 166–169
hardware components, 73
technical specification, 78
Artificial neural networks,
 xviii
ATmega2560
 microcontroller,
 165–166
Atmospheric sensors,
 technical specification
of, 62, 63
Battery life, 69–70
Battery power
 consumption
 calculation, 71
BIS Research, 58–59
Brioagrow, 8–9, 14
Broccoli (*Brassica
oleracea*)
 plantation of, 4–7
producers, in Mexico,
 44–47
Business user case,
 84–86
Campeche, 35
Cargill, 20–21
Chiapas, 36
Coahuila, 36
Colima, 36

- Comma-separated value (CSV), 119–120, 123, 125–127, 129, 131–132, 143–144
- Crop menu sequence, 99
- Crop user case description, 87–88
- Data acquisition (DAQ) system, 114–115, 117
- Database (DB) creation, 1–3 development and implementation of, 3–4 sequence, filling, 99 user case description, filling, 90, 92, 96
- Data mining, 1–3
- DHT22 sensor, 146–147, 155, 156–157
- Differentiated integral processes, xviii
- Direct sowing, 21, 24–25 advantages of, 24 disadvantages of, 24–25
- DS3231 RTC, 155–156
- Durango, 37
- EC-05 (soil moisture sensor), 61–65
- Electrical conductivity (EC) measurement, 127–135
- Employee administration user case description, 92, 97
- Employee management sequence, 99
- Entity-relationship diagram (ERD), 98, 101
- 5TE sensor probe, 129–130, 131–132, 133–134, 135, 145–146, 152–153
- STM (soil temperature and moisture sensor), 60–61
- Fuzzy logic, xviii
- Geographical information system (GIS), 22–23
- Global positioning system (GPS), 22–23, 53–54, 58–59
- Global radiation measurement, 136–141
- Graphical user interface (GUI), 164
- GS3 (electrical conductivity sensor), 61
- Guanajuato, 37
- Guerrero, 37–38
- Hardware brain, 73–80
- Arduino Mega 2560, 76–77, 78
- Raspberry Pi 3 Model B, 74–76
- XBee PRO Series 1, 77–80
- HCI, 99–101
- Hidalgo, 38
- Hierarchical control model, 50–51

- Historic data use case diagram, 86–87
- HMP-60 (humidity and temperature probe sensor) sensor, 60, 121, 136–137
- configuration values, 123–124
- HoneyComb, 9–10, 14
- Humidity measurement, 120–127
- Hybrid seeds, 20
- IEEE 802.15.4 standard XBee PRO Series 1, 78, 79–80
- Intellectual property analysis, 28–33
- computer programs, protection of, 30–33
- Internal control models, xx–xxi
- Jalisco, 38
- LM355 sensor, 165
- MakeMap™ Processing, 9–10
- Matplotlib software, 164, 167–169
- Monsanto, 20–21
- Morelos, 38
- Nayarit, 39
- Non-linear control systems, 49–50
- Nuevo León, 39
- Oaxaca, 39
- Optimal control systems, 49–50
- Outside temperature measurement, 120–127
- Planting techniques, 21–22
- Prediction models, xix–xx, xx, xxi–xxii
- Proagro Productivo, 34
- Production control, xix–xx, xx, xxi–xxii
- Proof-of-concept activities, 118–141
- Puebla, 39
- Qualcomm, 30–31
- Querétaro, 39
- Quintana Roo, 39–40
- Raspberry Pi 3 Model B, 67, 74–76, 118–120, 123–124, 125–127, 129, 133–134, 135, 137, 140–141, 143–145, 160–161, 163, 164, 166–169
- hardware components, 73
- software, 126–127
- technical specification of, 75
- Remote control agriculture, 22
- Sagarpa, 34–42
- San Luis Potosí, 40

- Sensor nodes (SNs), 114, 115–116, 117
Sensors, 22–23, 55–65
atmospheric sensors,
technical specification
of, 62, 63
EC-05 (soil moisture
sensor), 61–65
5TM (soil temperature
and moisture sensor),
60–61
GS3 (electrical
conductivity sensor),
61
HMP-60 (humidity and
temperature probe
sensor), 60
sequence management, 99
soil sensors, technical
specification of,
62–65
SP-212 (solar radiation
sensor), 60
use case description,
management of,
89–90, 95
Sinaloa, 40
Sink nodes, 65–67
structure of, 65–66
Sismagro, 11–12, 14
Smart Agriculture, xviii
Smart Fertilizer
Management Software,
10–11, 14
Smart monitoring and
control system
(SMCS), 99–101,
111–112, 114–116
- Soil
compaction, 16, 17
erosion, 16
moisture, 127–129
productivity improvement
techniques, 16
sensors, technical
specification of,
62–65
temperature
measurement,
127–135
Solar panels, 67–73
battery power
consumption
calculation, 71
technical specification of,
72
V44 batteries, 72
Sonora, 40
SPI-212 sensor, 60,
137–140, 146–147
System architecture,
49–52
hardware brain,
73–80
Arduino Mega 2560,
76–77, 78
components, 73
Raspberry Pi 3 Model B,
74–76
XBee PRO Series 1,
77–80
wireless sensor network,
52–73
sensors, 55–65
sink nodes, 65–67
solar panels, 67–73

- Tabasco, 41
Tamaulipas, 41
Technology readiness level (TRL), 115–116, 157–161
Tlaxcala, 41
Transgenic seeds, 20–21, 27–28
advantages of, 27–28
disadvantages of, 28

UAA, 115–116
University of Derby (UoD), 115–116

V44 batteries
 Arduino runtime from, 72
 technical specification of, 72
VegHands, 7–8, 14
Veracruz, 41–42
Volumetric water content (VWC), 60–61

Water conservation, 111
Wireless sensor network (WSN), 52–73, 84, 113–114, 115–118, 163, 164, 166

description and functions, 85
sensors, 55–65
 EC-05 (soil moisture sensor), 61–65
 5TM (soil temperature and moisture sensor), 60–61
 GS3 (electrical conductivity sensor), 61
 HMP-60 (humidity and temperature probe sensor), 60
 SP-212 (solar radiation sensor), 60
structure of, 54
system architecture of, 55

XBee PRO Series 1, 59, 67, 77–80, 121, 163, 164, 165, 166, 167
hardware components, 73

Yucatán, 42

Zacatecas, 42
Zigbee network, 118
Zigbee S2C modules, 141–142, 143